

Liquids to Value

**GEA Tuchenhagen®-VARIFLOW**  
**Kreiskolbenpumpen VPSH**  
*Rotary Piston Pumps VPSH*



*selbstsaugend / self-priming*

	VPSH 32	VPSH 34	VPSH 42	VPSH 44	VPSH 52	VPSH 54	VPSH 62	VPSH 64	VPSH72	VPSH74	VPSH76
max. Fördermenge [m <sup>3</sup> /h] <i>max. flow rates [m<sup>3</sup>/h]</i>	3,12	6,3	7,38	12,24	15,9	27,3	27,66	41,04	50,16	73,8	108,54
max. Förderhöhe [m] <i>max. pump heads [m]</i>	150	80	150	80	150	80	150	80	150	80	50
Liter pro 100 Umdrehungen <i>capacity (l/100 rpm)</i>	3,5	7	12,3	20,4	26,5	45,5	64	95	123	205	301,5
max. U / min. <i>max. speed rpm</i>	1.500	1.500	1.000	1.000	1.000	1.000	720	720	680	600	600
max Viskosität mPas <i>max viscosity mPas</i>	1.000.000										
Anschluss ID <i>connection</i>	3/4"	1"	1"	1 1/2"	1 1/2"	2"	2 1/2"	3"	3"	4"	5"